

Nginx Conf

```
server {
    listen 443 ssl http2;
    listen [::]:443 ssl http2;
    listen 80;
    server_name [];

    ssl_certificate SSL[]/cert.pem;
    ssl_certificate_key SSL[]/key.pem;

    add_header X-Frame-Options "SAMEORIGIN" always;
    add_header X-XSS-Protection "1; mode=block" always;
    add_header X-Content-Type-Options "nosniff" always;
    add_header Referrer-Policy "no-referrer-when-downgrade" always;
    add_header Content-Security-Policy "default-src * data: 'unsafe-eval' 'unsafe-inline' "
always;
    add_header Strict-Transport-Security "max-age=31536000; includeSubDomains; preload"
always;

    location / {
        proxy_pass []IP;
        proxy_connect_timeout 300s;
        proxy_read_timeout 300s;
        proxy_send_timeout 300s;
        proxy_set_header    Host                $host:$proxy_port;
        proxy_set_header    X-Real-IP           $remote_addr;
        proxy_set_header    X-Forwarded-For     $proxy_add_x_forwarded_for;
        proxy_set_header    Via                 "nginx";
    }
}
```

--	--	--	--

```
vim /etc/nginx/sites-enabled/nginx
```

■■■■■■■■

■■■■■■

systemctl reload nginx

Revision #2
Created 30 December 2022 15:09:44 by ■■
Updated 17 February 2023 21:22:12 by ■■